SKG Foam pourer

Foam pourer SKG type, execution for welding inside the tank or on the splash board,
for fixed installation on top pouring systems,
for mounting downstream heavy foam making branchpipes L type,
- body in welded carbon steel plate / carbon steel pipe,
- inlet welding pipe API 5L grade B schedule 40,
- external protective painting: sandblasting SA 2,5, n.1 epoxy primer coat d.f.t.≥40µ,
  n.2 final polyurethanic coat red RAL 3000, d.f.t. ≥30µ each,
  total d.f.t. ≥100µ

Welding execution						
Type	Code nr.	Matching branchpipe	Matching foam chamber	Inlet welding pipe	Weight (Kg)	Dwg. nr.
SKG 80	0401080220	L2st or L4st		3"	4.5	04010110
SKG 100	0401100220	L8st or L10st	STO 2	4"	4.5	04010110
SKG 125	0401125020		STO 4	5"	4.5	04010110
SKG 150	0401150220	L12st or L16st	STO 8	6"	9.0	04010110
SKG 200	0401200220	L20st, L24st or L32st		8"	9.0	04010110
SKG 250	0401250220		STO 12/16	10"	13.0	04010110
SKG 300	0401300220		STO 24/32	12"	13.0	04010110

Caccialanza & C. reserves the right to change or modify without previous notice any data or specification due to changes or modification in order to improve the products presented.